



TOOL TETHERING + LANYARDS

Drop Free Zone

Squids 3108F(x) Tool Lanyard Single Locking Carabiner 6.8kg



- » Approved to the ANSI/ISEA 121-2018 standard
- » Shock absorbing properties reduce the dynamic force on the body or other anchor point if drop occurs
- » Durable 1680 denier polyester elastic blended webbing extends from 96-122cm
- » Low profile lightweight design reduces snag hazards and added weight
- » Anodized aluminum alloy carabiner with double action locking gate and inherent captive eye
- » Ergonomic carabiner is designed for easily gripping and handling with gloves
- » Treaded loop end that grips the tool when attached
- » High strength 3-ply nylon stitching secures connecting ends
- » Single length construction eliminates weak points seen with multi-component lanyards

The **Squids 3108F(x) Tool Lanyard Single Locking Carabiner** is a shock absorbing tool lanyard with locking carabiner on one end and loop on the other end. Designed and tested to prevent falling objects and reduce the force your body sees if a drop occurs by absorbing the energy transmitted through the tool lanyard. By reducing the shock load this design prevents the tool from pulling the user down with it protecting those above as well as those below.

TESTED TO BE TRUSTED

All lanyards are rigorously tested and third party certified to a 6.8kg maximum capacity with a 2:1 safety factor to prevent falling objects. When working at heights, choosing the best tool tethering equipment matters because there are no second chances.

DROPPED OBJECTS STANDARD 121-2018

The ISEA/ANSI Dropped Objects Standard provides guidelines to protect workers from hazardous dropped objects. It outlines requirements for personal protective equipment, procedures, and systems to reduce the risk of injury from falling objects.

DIMENSIONS
96-122cm

WEIGHT RATING
6.8kg



SCAN TO ORDER

PART NO.	DESCRIPTION
19808	Squids 3108F(x) Tool Lanyard Single Locking Carabiner