



TOOL TETHERING + LANYARDS

Drop Free Zone

Squids 3109F(x) Double-Locking Tool Lanyard 11.3kg



- » Approved to the ANSI/ISEA 121-2018 standard
- » Shock absorbing properties reduce the dynamic force on the body or other anchor point if drop occurs
- » Durable 1680 denier polyester elastic blended webbing extends from 96-122cm
- » Low profile lightweight design reduces snag hazards and added weight
- » Anodized aluminum alloy swiveling carabiner with double action locking gate and inherent captive eye
- » Ergonomic carabiner is designed for easily gripping and handling with gloves
- » Treaded loop end that grips the tool when attached
- » High strength 3-ply nylon stitching secures connecting ends
- » Single length construction eliminates weak points seen with multi-component lanyards
- » Patent pending design

The **Squids 3109F(x) Double-Locking Tool Lanyard** is shock absorbing tool lanyard with swiveling, locking carabiner on one end and loop on the other end. Designed and tested to prevent falling objects and reduce the force the anchor point sees if a drop occurs by absorbing the energy transmitted through the tool lanyard. Swiveling design helps prevent tangles and binding.

TESTED TO BE TRUSTED

All lanyards are rigorously tested and third party certified to a 11.3kg maximum capacity with a 2:1 safety factor to prevent falling objects. When working at heights, choosing the best tool tethering equipment matters because there are no second chances.

DROPPED OBJECTS STANDARD 121-2018

The ISEA/ANSI Dropped Objects Standard provides guidelines to protect workers from hazardous dropped objects. It outlines requirements for personal protective equipment, procedures, and systems to reduce the risk of injury from falling objects.

↔ **DIMENSIONS**
96-122cm

🏋️ **WEIGHT RATING**
11.3kg



SCAN TO
ORDER

PART NO.	DESCRIPTION
19809	Squids 3109F(x) Tool Lanyard - Double-Locking Swivel Carabiner & Loop